

TRANSMITTER POCKET



TECHNICAL SALES SHEET

Transmitter Type: POCKET

- **Housing:**
Ergonomically designed housing, one-hand operation
- **Housing Material:**
Polycarbonate (PC) blend
- **Environmental Protection:**
IP65
- **Weight:**
200 g (0.4 lbs) includes batteries
- **Dimensions:**
Length: 123 mm, (4.8 in)
Height: 69 mm, (2.7 in)
Depth: 28 mm, (1.1 in)
- **Battery Compartment:**
Separated from electronics, with sliding, heavy-duty lid
- **Power Supply:**
3 AA batteries (3 Mignon LR6-AA 1.5V)
- **Diagnostics:**
Status LED for operation, low battery and Stop activation
- **Operation Time:**
Up to 20 h continuous transmission
- **Pushbutton Configuration:**
 - V1 - 2 dual speed + start/horn + stop
 - V2 - 4 dual speed + start/horn + stop
 - V3 - 6 single speed + start/horn + stop
 - V4 - 3 single speed + stop
 - V5 - 6 dual speed + start/horn + stop
- **Frequency Range:**
868 MHz / 916 MHz, 2.4 GHz
- **RF Unit:**
Type MFS with single frequency, selectable duty cycle
- **Power (RF Output):**
< 25mW
- **Typical Operating Range:**
868 MHz / 916 MHz - up to 30m (100 ft)
MFS 2.4 GHz / 2.4 GHz - up to 70m (230 ft)
- **Safety Address:**
 - 20-bit (over 999,999 individual possibilities)
Permanently assigned in transmitter
Address learning receiver
- **Safety:**
Active and passive Stop function
Parity & Checksum
- **Temperature Range:**
-25°C to 70°C (-11°F to 158°F)
- **Humidity Range:**
0 - 97% non-condensing
- **Response Time:**
Less than 100 msec.
- **Baud Rate:**
Up to 76.8 Kbps. (selectable via H-Link)

